



STORAGE




FABMATICS

Automate your success

# FOUP PURGE SYSTEM

Retrofittable inert gas purge system for FOUP storage bins



# FOUP PURGE SYSTEM


Retrofittable inert gas purge system for FOUP storage bins

Semiconductor industry leading edge companies are developing and producing at process nodes of 28 nm and below. These smaller structures require a contamination and oxidation-free environment during production in order to exclude harmful influences like humidity, ambient oxygen or emission of molecules (airborne molecular contamination). These process related interactions may lead to surface defects and yield loss.

Especially while wafers stored in FOUPs are waiting for the next process step, the danger of these unwanted side reactions is very high. Our purge system **avoids oxidation and other chemical reactions** by purg-

ing the FOUP with an inert gas during interim storage between two process steps. The system can be **easily retrofitted to existing storage bins** (e.g. Zero Footprint Storage) in cleanrooms. The advantage in this case versus the exclusive use of purgeable loadports, which can only flush the FOUP with gas during docked on process tools, is the **continuing supply of an inert gas** like nitrogen at any conceivable storage location by using an economical flowrate. This is triggered as soon as the FOUP is deposited and ends once it will be removed from the nest again. This reliably protects the wafers during the entire storage period.

## General system design



Application example for Zero Footprint Storage

### The purge system consists of three main components:

- Advanced Purge Nest Unit (APNU)
- Purge Bay Controller (PBC)
- Purge Manager Software

Every Zero Footprint Storage bin can be retrofitted with an **Advanced Purge Nest Unit (APNU)** which is used to accommodate the purge inlet interfaces. They directly communicate via a combined CAN power bus wire with the **Purge Bay Controller (PBC)**. The PBC controls up to 108 APNU modules and is responsible for the communication to the **Purge Manager Software**. Each Purge Bay Controller has its own IP address for individual access with a Service GUI via a standard web browser and optional via HSMS.

# Features

## Easy to retrofit

- May be retrofitted on existing systems for FOUN storage (e.g. ZFS, stocker) without having to change the fab structure
- Installation during regular operations possible

## Flexible installation

- APNU modules can be installed wherever necessary, in rows, isles or in a matrix
- Quick servicing possible

## No additional footprint needed

- Purge nests are integrated into existing storage bins
- Slim, light & functional design

## High purity operation


- Advanced purge interface design provide maximum pureness and durability
- Each APNU features its own particle filter

## Intelligent software

- Every purge nest is individually monitored and controlled
- Sensors in the nest monitor the gas flow via back pressure and report errors
- Independent purge functionality for each nest, no gas spill / waste
- Interval purge functionality can set up via purge profiles
- Service GUI via web interface
- Continuous quality monitoring in combination with Advanced Qualification FOUN (optional)
- Lean and flexible control system based on embedded Linux
- HSMS interface based on SEMI E88 (optional)

## General characteristics


- Silent noise free purge operation on any condition



More than 7,000 FOUN purge bins already in operation (here: application example at GLOBALFOUNDRIES Dresden)

# Benefits

- Avoids AMC (Airborne Molecular Contamination) and other chemical reactions



- Allows extended queue time between process steps



- Improves overall process yield
- Minimized cost of ownership by optimized long term durability of all components

# Technical data

## Advanced Purge Nest Unit (APNU)

Placement sensor	Optical LiDAR-TOF
Flow rate	3 slpm by default, divergent upon request
Supported FOUN types	Entegris Spectra (rear purge), others upon request
No. of interfaces	1 or 2, upon request
Pressure sensor	Software defined switch points detect multiple back-pressure ranges (e.g. low, good, high)
Weight	1 kg / 2.2 lb
Material (baseplate)	Anodized aluminium
Features	Multi LED status display, Qualification FOUN IR data link

## Purge Bay Controller (PBC)

Amount of connectable APNUs	108
Communication uplink	Web GUI and HSMS (optional) via Ethernet
Operation system	Embedded Linux
Weight	6 kg / 13.2 lb
Material (case)	ABS plastic
Features	Web GUI provides overall pressure, flow and utilization monitoring

**STORAGE**  
ZERO FOOTPRINT STOCKER  
PURGE SYSTEMS  
RFID RACKS



**HANDLING**  
MOBILE ROBOTS  
ROBOT CELLS  
EFEMS



**TRANSPORT**  
CONVEYOR SYSTEMS  
AGVS / RGVS  
PGVS



# UNIQUE PRODUCT PORTFOLIO FOR THE **COMPLETE MATERIAL HANDLING AUTOMATION**



**IDENTIFICATION**  
RFID SYSTEMS  
RFID RETROFITTING  
RFID BASED LOGISTICS SYSTEMS



**SOFTWARE**  
FLEET MANAGER FOR MOBILE ROBOTS  
SOFTWARE INTEGRATION  
WEB GUIs



**SERVICE**  
CONSULTING & FEASIBILITY STUDIES  
TECHNICAL SERVICES  
THIRD PARTY SUPPORT



[www.fabmatics.com](http://www.fabmatics.com)

## Europe

Headquarters Dresden  
Phone: +49 351 65237-0  
E-mail: [info@fabmatics.com](mailto:info@fabmatics.com)

## USA

Location Salt Lake City  
Phone: +1 801 7480476  
E-mail: [info.usa@fabmatics.com](mailto:info.usa@fabmatics.com)

## Partners in Asia

Singapore & Malaysia  
Phone: +65 9106 2386  
E-mail: [joseph.soo@micro-optics.com.sg](mailto:joseph.soo@micro-optics.com.sg)

## Taiwan

Phone: +886 912531863  
E-mail: [jeff.chen@gbgtek.com.tw](mailto:jeff.chen@gbgtek.com.tw)

## China

Phone: +86 13910374221  
E-mail: [jeff.chen@gbgtek.com.tw](mailto:jeff.chen@gbgtek.com.tw)